



Wireless Solutions for Fire & Security

FireCell Input / Output Unit

- Fully addressable
- Wireless activation
- Third party approved (EN54)
- 2-way radio communication
- IP65 casing
- 5 year battery life at normal conditions
- Dual input option
- Dual output option
- Universal transmitter module
- Transmitter tamper
- Range in excess of 150 metres



Overview

The model FC-600-001 Input/Output unit is a battery operated device remotely activated and monitored by the node network.

Model FC-610-001 has dual inputs and outputs that can be individually operated whilst using only one address on the system.

The device is housed in an industry standard, impact resistant ABS moulding and has 2-way radio communication with the fire system controller using 868MHz wavebands to receive command instructions for auto reporting.

Designed and manufactured using the latest techniques and surface-mount technology ensures component count is kept to a minimum, thereby maximising reliability.

The I/O unit is powered by a low-voltage dual supply alkaline battery pack. The battery pack condition is continually monitored. The battery board has been tested to provide a 5 year battery life at normal conditions. The system indicates remaining battery capacity and a low battery condition is indicated to the controller as a fault, leaving approximately 30 days for the battery pack to be changed.



Specification

Dimensions:	240 x 120 x 50mm Weight 0.60Kg
Operating Temperature:	-10 to +55 °C
Humidity:	Up to 95% non-condensing
Supply:	6 x AA cell Duracell Alkaline batteries
IP Rating:	IP65
Output Rating:	2A @24V DC.
Operating Frequencies:	868 MHz
Output Transmitter Power:	Variable 0-14dBm
Standards:	Third party certified to; EN54 part 18 EN54 part 25 ENTSI 300:220

Ordering Information

Single I/O Unit
Dual I/O Unit
Aux. relay module 2 x 230V 2amp
relays

Part Number **FC-600-001**
Part Number **FC-610-001**
Part Number **FC-620-001**



EMS Group Head Office
Technology House
Sea Street
Herne Bay
Kent CT6 8JZ
England
Tel: +44 (0) 1227 369570
Fax: +44 (0) 1227 369679
Email: enquiries@emsgroup.co.uk

www.emsgroup.co.uk

An ISO9001:2008 approved company



Dealer Information:

The information contained within this literature is correct at time of publishing. The EMS Group reserves the right to change any information regarding products as part of its continual development enhancing new technology and reliability. The EMS Group advises that any product literature issue numbers are checked with its head office prior to any formal specifications being written.

Part No: Firecell 7, v1.4